

Indoor Camera

Monitor and protect your home

Heimgard Technologies

With a Wi-Fi indoor surveillance camera, you can peek into your home or cabin when you're away. This security camera is both practical and discreet. Check that your pet is doing well at home, or verify what has happened if a security sensor is triggered.

Production data

- Version: V2
- Model no.: 127103
- El-number (NO): NA
- Product category: Alarm and security
- Sub category: Surveillance
- GTIN (EAN): 7090026462534
- SKU/Art.no: HT-INDOOR-4

Communication network

- Network interface: Wi-Fi
- Supported Wi-Fi Bands: 2.4gHz
- Wi-Fi Generation: Wi-Fi 5 (802.11ac)
- Subscription Required: No (Optional for cloud storage)

Communication smart home

- Requires smart home hub: Yes
- RF communication protocol: Wi-Fi
- Range Extender (Mesh): No
- ONVIF compliant: Yes
- Max wireless range (meter): 50OTA Update Support: Yes

- App control
- App control: Yes
- (When connected to a Heimgard hub.) • Name of available app (s): Heimgard app
- · Maine of available app (S). Heinigard app

Features

- Max video recording resolution: 1080p - FHD (1920x1080)
- Night vision (m): 10
- Audio: Microphone (Not supported in app
- Livestream in app: Yes
- Storage options: Cloud storage (Subscription Required)
- Digital Zoom (x): 16 (Not relevant for app)
- Lens (mm): 3.6
- Horizontal viewing angle (°): 86
- Vertical viewing angle (°): 45
- Diagonal viewing angle (°): 105
- Motorized Pan/Tilt: No
- Sensor range (m): 10
- Built-in Sensors / Detectors: No
- Number of Buttons: 1

Key features

- Easy DIY installation
- Minimalistic design
- ONVIF compliant
- 1080p Full HD recording resolution
- Night vision

Order no.: 127103

Heimgard Indoor Camera Ver: 1.0 - Copyright©2021. All data is subject to change without notice.

Heimgard Technologies

Sensors and alarms

Indoor Camera

Monitor and protect your home

Power

- Primary power source: Power adapter DC5V1A (110 230V)
- · Length of power cord (cm): 3
- Voltage (V): 110 230V
- Device Reports Consumption Data: No
- · Secondary power source (Back-up): No

Placement and operation temperature

- Operating temperature (°C): -10°C~+45°
- Field of application: Indoors
- Operating Relative Humidity (%): <95% RH
- · Mounting options: Stand, Screws
- Placement: Wall, Ceiling, Table
- Requires Authorized Installer: No

Dimensions and weight

- Dimensions HxWxD (cm): 6.80 x 3.30 x 10.66
- Net weight (g): 90.5
- Net weight pr unit (g): 90.5

Materials and colors

· Finish: Plastic

· Color: White

Logistics and packaging

- Dimensions F-PAK HxWxD (cm): 17.35 x 9.05 x 7.80
- Dimensions D-PAK HxWxD (cm): TBC
- Gross weight F-PAK (g): TBC
- · Gross weight D-PAK (kg): TBC
- Quantity in sales pack (F-PAK): 1
- Quantity in carton (D-PAK): TBC
- Storage Temparature (°C): 10-35°C
- Storage Humidity (%): 30-50%RH (No Condensation)

Package content

- · Main product
- User manual
- Mounting bracket

Certifications

• CE. FCC

Security

- Power adapter Cable
- Installation position map

- IP Classification: IP20
- · Grounding: No

