## Sensors and alarms



# **Outdoor Camera**

Monitor and protect your property

With an IP65 certified Wi-Fi outdoor security camera, you can monitor your driveway, garage or any outdoor areas. Keep your property or holiday home safe, check the weather conditions or be notified if uninvited guests arrives.

## Production data

- Version: V2
- Model no.: 127105
- El-number (NO): NA
- Product category: Alarm and Security
- Sub category: Surveillance
- · GTIN (EAN): Outdoor camera
- SKU/Art.no: HT-OUTDOOR-4

## Communication network

- · Network interface: Ethernet | Wi-Fi
- · Supported Wi-Fi Bands: 2.4gHz
- · Wi-Fi Generation: Wi-Fi 5 (802.11ac)
- Subscription Required: No (Optional for cloud storage)

## Communication smart home

- · Requires smart home hub: Yes
- RF communication protocol: Wi-Fi
- Range Extender (Mesh): No
- · ONVIF compliant: Yes
- Max wireless range (meter): 50
- OTA Update Support: Yes

## App control

- App control: Yes
  (When connected to a Heimgard hub.)
- Name of available app (s): Heimgard app

## Features

- Max video recording resolution: 1080p - FHD (1920 x 1080)
- Night vision (m): 10
- Audio: Microphone (Not supported in app)
- · Livestream in app: Yes
- Storage options: Cloud storage (Subscription Required)
- Digital Zoom (x): 16 (Not relevant for app)
- Lens (mm): 2.8
- Horizontal viewing angle (°): 98
- Vertical viewing angle (°): 52
- Diagonal viewing angle (°): 115
- · Motorized Pan/Tilt: No
- · Sensor range (m): 30
- · Built-in Sensors / Detectors: No
- · Number of Buttons: 1

## Key features

- Easy DIY installation
- External antennas for optimal signal coverage
- ONVIF compliant
- 1080p Full HD recording resolution
- Night vision

Order no.: 127105





# **Outdoor Camera**

## Monitor and protect your property

### Power

- Primary power source: Power adapter DC12V0,5A (110 230V)
- Length of power cord (cm): 3
- Voltage (V): 110 230 V
- Device Reports Consumption Data: No
- · Secondary power source (Back-up): No

### Placement and operation temperature

- Operating temperature (°C): -30°C~+60°
- · Field of application: Outdoors
- Operating Relative Humidity (%): <95% RH
- · Mounting options: Screws
- · Placement: Wall, Ceiling
- · Requires Authorized Installer: No

### Dimensions and weight

- Dimensions HxWxD (cm): 14.77 x 7.42 x 7.42
- Net weight (g): 240
- Net weight pr unit (g): 240

## Materials and colors

Finish: Plastic

· Color: White

### Logistics and packaging

- Dimensions F-PAK HxWxD (cm): TBC
- Dimensions D-PAK HxWxD (cm): TBC
- · Gross weight F-PAK (g): TBC
- · Gross weight D-PAK (kg): TBC
- Quantity in sales pack (F-PAK): 1
- Quantity in carton (D-PAK): TBCStorage Tempurature (°C): 10-35°C
- Storage Humidity (%): 30-50%RH (No Condensation)

## Package content

- · Main product
- User Manual
- Mounting bracket
- Power Adapter
- Screws
- Installation Position Map

### Certifications

· CE, FCC

## Security

• IP Classification: IP67

· Grounding: No

