

Rotary Dimmer

Smart dimmer, 500 watt white



Trailing edge smart dimmer. Control your lights locally from the on-wall dimmer knob, or from anywhere by the app when connected to your Heimgard smart home system. Replacable service pack for dark finish sold separately.

Production data

- Version: V1
- Model no.: 118392
- EI-number (NO): 1403705
- Product category: Indoor climate and lighting
- Sub category: Remote control
- Product model: Dimmer
- GTIN (EAN): 7090026461254
- SKU/Art.no: HC-RDIMW-1

Communication network

- Subscription required: No

Communication smart home

- Requires smart home hub: Yes
- RF communication protocol: Zigbee 3.0
- Range Extender (Mesh): Yes (Zigbee)
- Max wireless range (meter): 30 (open range)
- OTA Update Support: Yes
- Voice control support: Yes (When connected to a Heimgard Hub. Voice assistant is not included)

App control

- App control: Yes
(When connected to a Heimgard hub.)
- Name of available app (s): Heimgard app

Features and available accessories

- Built-in sensors / detectors: No
- Function Keys (Actions): On/Off, Dim
- Available accessories: 120996

Materials and colors

- Finish: Plastic
- Color: White

Technical specifications

- Maximum Cross Section (mm²): 2,5
- Actuator type: Dimmer
- Dimmer technology: Trailing Edge
- Bypass Included: Yes

Dimensions and weight

- Dimensions HxWxD (cm): 8,38 x 8,38 x 4,71
- Net weight (g): 119
- Net weight pr unit (g): 119

Key features

- ▶ Trailing edge
- ▶ 20-500W capacitive load
- ▶ 3-250W resistive load
- ▶ Bypass included

Order no.: 118392

Rotary Dimmer

Smart dimmer, 500 watt white

Electrical Specifications

- Primary power source: Part of fixed installation
- Voltage (V): 100 - 240VAC
- Power Min. Resistive Load (W @230V): 20
- Power Max. Resistive Load (W @230V): 500
- Power Min. Capacitive (LED) Load (W @230V): 20
- Power Min. Capacitive Load w. Bypass (W @230V): 3
- Power Max. Capacitive (LED) Load (W @230V): 250
- Power Min. Inductive Load (W @230V): 20
- Power Max. Inductive Load (W @230V): 250
- Max Load (A ~ V): 2,2A ~ 230V
- Device Reports Consumption Data: Yes
(When connected to a Heimgard Hub)

Placement and operation temperature

- Field of application: Indoors
- Operating temp. (°C): -12 – +50
- Mounting options: Screws
- Screw Distance c-c (mm): 60
- Placement: Wall (integrated)
- Requires Authorized Installer: Yes
- Type of Junction Box: Single
- Integration depth (mm): 27,4
- Terminal connection type: Spring Cage Terminals

Certifications

- CE, FCC, ROHS

Logistics and packaging


- Customs Tariff Number (HS-Code): 8536.50.0000
- Country of origin: China
- Dimensions F-PAK HxWxD (cm): 11.5 x 11 x 5.8
- Dimensions D-PAK HxWxD (cm): 36.5 x 35 x 35
- Gross weight F-PAK (g): 256
- Gross weight D-PAK (kg): 12
- Quantity in sales pack (F-PAK): 1
- Number of F-PAK in D-PAK (carton): 45
- Minimum order quantity: 45
- Product Lifecycle: Active

Package content

- Main Product
- Dimmer Knob
- Bypass
- User Manual

Safety & security

- Grounding: No
- IP Classification: IP20
- Phase break (single/dual): 1-pole
- Protection class: 2
- Halogen-free: Yes



You can control more than 2 000 products from leading brands like Ikea, Samsung, Google and many, many more with the Heimgard Smart Home app. Available in Apple Store and Play Store.